

DWB-3.2 Jema Tyre changer



Jema Autolifte Tyre changer DWB-3.2

Basic Line Tyre changer DWB-3.2 is suitable for the professional workshop. DWB-3.2 has two assisting arms, tilting tower mounted tyre inflator and air booster.

The two assisting arms make working with alloy wheels easily and safely and minimize the risk of scratching a rim. The tyre changers has centerflange and can manage wheels from 10"-30"so the consumer will never have problems large or run-flat wheels.

Optional Extras adapters for motorcycles and plastic mounting head so the consumer does not scratch the rims.

Jema tyre changer DWB-3.2 has CE approval certificate!

Technical specifications

- Noise level 70db
- 220V power supply
- Motor power 1.1kW
- Air pressure 8-10bar
- Max. wheel diameter 48"
- Max. wheel width 20"
- Max. rim diameter 10-30"
- Tyre changer weight: 367kg
- CE Approved

Mounting/Demounting head

DWB-3.2 is produced with a metal mounting head but incl. plastic protection kit. Plastic mounting head is Optional.

Centerflange

DWB-3.2 has a center flange which does it can manage rims from 10"-30"
DWB-3.2 comes with different adaptors.

Tyre inflator

DWB-3.2 comes with tyre inflator and airbooster.

Two assisting helping arm and lifting platform

DWB-3.2 has two assisting helping arms, with central locking device. The assisting helping arms makes it easier to work with run flat tyres. Another feature on the DWB-3 is a lifting platform to assure the user a easier and less stressful working day!



DWB-3.2 is Fully automatic pneumatic tilting column, pneumatic locked at optional position. Powerful air booster makes the tyre and rim jointed instantly. DWB-3.2 is suitable for low profile tyres. The tyre changer DWB-3.2 is CE approved

